

Model			CS/CU-HU12XKYF
Tonnage Class		T	1.0
Cooling Capacity Standard [Min. - Max.]		Btu/h	11942 [5374 - 13136]
		W	3500 [1575 - 3850]
ISEER		-	4.70
Annual Power Consumption		kWh	576.26
Star Rating		★	5
Electrical Data	Voltage	V	230
	Running Current	A	4.2
	Power Input Standard Cooling [Min. - Max.]	W	915 [320 - 1200]
Moisture Removal Rate		l/h	1.0
		Pt/h	2.1
Air Circulation (Indoor/Hi)		m³/min	13.5
		ft³/min	477
Net Dimensions IDU	Length (L)	cm	87.0
	Breadth (B)	cm	23.6
	Height (H)	cm	29.6
Net Dimensions ODU	Length (L)	cm	82.4
	Breadth (B)	cm	29.9
	Height (H)	cm	61.9
Noise Level	Indoor (H/L)	[dB-A]	43/38
	Outdoor	[dB-A]	51
Net Weight	IDU [ODU]	kg	9 [26]
	IDU [ODU]	lb	20 [58]
Refrigerant			R-32
Operating Temp. Range		°C	16 ~ 52
Operating Volt. Range		V	145 - 285
Refrigerant Pipe Diameter	Liquid Side	cm	Ø0.635
	Gas Side	cm	Ø1.270
Pipe Extension	Chargeless Pipe Length	m	7.5
	Maximum Pipe Length	m	10
	Maximum Elevation Length	m	5
	Additional Refrigerant Gas *	g/m	10